

## **Factors Assessed in Watershed Evaluations**

### **Water Quality**

The Water Program comprises activities within SCDHEC's Bureau of Water and Bureau of Environmental Services. The Program's objectives are to ensure that the water in South Carolina is safe for drinking and recreation, and that it is suitable to support and maintain aquatic flora and fauna. Functions include planning, permitting, compliance assurance, enforcement, and monitoring. This section provides an overview of water quality evaluation and protection activities.

### ***Monitoring***

In an effort to evaluate the State's water quality, the Department operates a permanent Statewide network of primary ambient monitoring stations and flexible, rotating secondary and watershed monitoring stations. The ambient monitoring network is directed toward determining long-term water quality trends, assessing attainment of water quality standards, identifying locations in need of additional attention, and providing background data for planning and evaluating stream classifications and standards.

The monitoring data are also used in the process of formulating permit limits for wastewater discharges with the goal of maintaining State and Federal water quality standards and criteria in the receiving streams in accordance with the goals of the Clean Water Act. These standards and criteria define the instream chemical concentrations that provide for protection and reproduction of aquatic flora and fauna, determine support of the classified uses of each waterbody, and serve as instream limits for the regulation of wastewater discharges or other activities. In addition, these data are used in the preparation of the biennial §305(b) report to Congress, which summarizes the State's water quality with respect to attainment of classified uses by comparing the ambient monitoring network data to the State Water Quality Standards.

SCDHEC's water quality monitoring network comprises three station types: primary (P), secondary (S), and watershed (W) stations. Primary stations are sampled on a monthly basis year round, and are located in high water-use areas or as background stations upstream of high water-use areas. The static primary station network is operated statewide, and receives the most extensive parameter coverage, thus making it best suited for detecting long term trends.

Secondary stations are sampled monthly from May through October, a period critical to aquatic life, characterized by higher water temperatures and lower flows. Secondary stations are located in areas where specific monitoring is warranted due to point source discharges, or areas with a history of water quality problems. Secondary station parameter coverage is less extensive and more flexible than primary or watershed station coverages. The number and locations of secondary stations have greater annual variability than do those in the primary station network, and during a basin's target year may have parameter coverage and sampling frequency duplicating that of primary or watershed stations.

Watershed stations are sampled on a monthly basis, year round, during a basin's target year; additional watershed stations may be sampled monthly from May through October to augment the secondary station network. Watershed stations are located to provide more complete and representative coverage within

the larger drainage basin, and to identify additional monitoring needs. Watershed stations have the same parameter coverage as primary stations.

Many pollutants may be components of point source discharges, but may be discharged in a discontinuous manner, or at such low concentrations that water column sampling for them is impractical. Some pollutants are also common in nonpoint source runoff, reaching waterways only after a heavy rainfall; therefore, in these situations, the best media for the detection of these chemicals are sediment and fish tissue where they may accumulate over time. Their impact may also affect the macroinvertebrate community.

Regional ambient trend monitoring is conducted to collect data to indicate general biological conditions of state waters which may be subject to a variety of point and nonpoint source impacts. In 1991, the Department began using ambient macroinvertebrate data to support the development of Watershed Water Quality Assessments. Ambient sampling is also used to establish regional reference or "least impacted" sites from which to make comparisons in future monitoring. Additionally, special macroinvertebrate studies, in which stream specific comparisons among stations located upstream and downstream from a known discharge or nonpoint source area, are used to assess impact.

Qualitative sampling of macroinvertebrate communities are the primary bioassessment techniques used in ambient trend monitoring. A habitat assessment of general stream habitat availability and a substrate characterization is conducted at each site. Annual trend monitoring is conducted during low flow "worst case" conditions in July - September. This technique may also be used in special studies for the purpose of determining if, and to what extent, a wastewater discharge or nonpoint source runoff is impacting the receiving stream. A minimum of two sample locations, one upstream and one downstream from a discharge or runoff area, is collected. At least one downstream recovery station is also established when appropriate. Sampling methodology essentially follows procedures described in Standard Operating Procedures, Biological Monitoring.

Aquatic sediments represent a historical record of chronic conditions existing in the water column. Pollutants bind to particulate organic matter in the water column and settle to the bottom where they become part of the sediment "record". This process of sedimentation not only reflects the impact of point source discharges, but also incorporates nonpoint source pollution washed into the stream during rain events. As a result, contaminant concentrations originating from irregular and highly variable sources are recorded in the sediment. The sediment concentrations at a particular location do not vary as rapidly with time as do the water column concentrations. Thus, the sediment record may be read at a later time, unrelated to the actual release time. Lakes act as settling basins for materials entering the lake system directly from a discharge or indirectly from the land surface washed into streams. Therefore, it is not unusual for lake sediment concentrations to be higher than sediment concentrations found in streams. This is especially true for chromium, copper, and zinc.

The ambient monitoring network, as a program, has the capability of sampling a wide range of media and analyzing them for the presence or effects of contaminants. Ambient monitoring data from 20 primary (P) stations, 14 secondary (S) stations (3 with increased coverage during the basin monitoring year), and 23 watershed (W) stations were reviewed for the Edisto River Basin, along with 22 biological (BIO) stations to assess macroinvertebrate communities.

### ***Classified Waters, Standards, and Natural Conditions***

The waters of the State have been classified in regulation based on the desired uses of each waterbody. State standards for various parameters have been established to protect all uses within each classification. The water-use classifications that apply to this basin are as follows.

**Class ORW**, or "outstanding resource waters", are freshwaters or saltwaters which constitute an outstanding recreational or ecological resource, or those freshwaters suitable as a source for drinking water supply purposes, with treatment levels specified by the Department.

**Class A** were freshwaters which were suitable for primary contact recreation. This class was also suitable for uses listed as Class B. As of April, 1992, Class A and Class B waters were reclassified as Class FW which protects for primary contact recreation.

**Class B** were freshwaters which were suitable for secondary contact recreation and as a source for drinking water supply, after conventional treatment, in accordance with the requirements of the Department. These waters were suitable for fishing, and the survival and propagation of a balanced indigenous aquatic community of fauna and flora. This class was also suitable for industrial and agricultural uses. The main difference between the Class A and B freshwater was the fecal coliform standard. Class A waters were not to exceed a geometric mean of 200/100ml, based on 5 consecutive samples during any 30 day period; nor were more than 10% of the total samples during any 30 day period to exceed 400/100ml. Class B waters were not to exceed a geometric mean of 1000/100ml, based on 5 consecutive samples during any 30 day period; nor were more than 20% of the total samples during any 30 day period to exceed 2000/100ml. As of April, 1992, Class A and Class B waters were reclassified as Class FW, which protects for primary contact recreation.

**Class FW**, or "freshwaters", are freshwaters which are suitable for primary and secondary contact recreation and as a source for drinking water supply, after conventional treatment, in accordance with the requirements of the Department. These waters are suitable for fishing, and the survival and propagation of a balanced indigenous aquatic community of fauna and flora. This class is also suitable for industrial and agricultural uses.

**Class SFH**, or "shellfish harvesting" waters, are tidal saltwaters protected for shellfish harvesting, and are suitable also for uses listed in Classes SA and SB.

**Class SA** comprises "tidal saltwaters" suitable for primary and secondary contact recreation, crabbing and fishing. These waters are not protected for harvesting of clams, mussels, or oysters for market purposes or human consumption. The waters are suitable for the survival and propagation of a balanced indigenous aquatic community of marine fauna and flora.

**Class SB** are "tidal saltwaters" suitable for the same uses listed in SA. The difference between the Class SA and SB saltwater concerns the DO limitations. Class SA waters must maintain daily DO averages not less than 5.0 mg/l, with a minimum of 4.0 mg/l, and Class SB waters maintain DO levels not less than 4.0 mg/l.

**Site specific numeric standards (\*)** for surface waters may be established by the Department to replace the numeric standards found in Regulation 61-68 or to add new standards not contained in R.61-68. Establishment of such standards shall be subject to public participation and administrative procedures for adopting regulations. In addition, such site specific numeric standards shall not apply to tributary or downstream waters unless specifically described in the water classification listing in R.61-69.

The standards are used as instream water quality goals to maintain and improve water quality and also serve as the foundation of the Bureau of Water's program. They are used to determine permit limits for

treated wastewater dischargers and any other activities that may impact water quality. Using mathematical Wasteload Allocation Models, the impact of a wastewater discharge on a receiving stream, where flow is unregulated by dams, is predicted using 7Q10 streamflows. These predictions are then used to set limits for different pollutants on the National Pollutant Discharge Elimination System (NPDES) permits issued by the Department. The NPDES permit limits are set so that, as long as a permittee (wastewater discharger) meets the established permit limits, the discharge should not cause a standards violation in the receiving stream. All discharges to the waters of the State are required to have an NPDES permit and must abide by those limits, under penalty of law.

Classifications are based on desired uses, not on natural or existing water quality, and are a legal means to obtain the necessary treatment of discharged wastewater to protect designated uses. Actual water quality may not have a bearing on a waterbody's classification. A waterbody may be reclassified if desired or existing public uses justify the reclassification and the water quality necessary to protect these uses is attainable. A classification change is an amendment to a State regulation and requires public participation, SCDHEC Board approval, and General Assembly approval.

Natural conditions may prevent a waterbody from meeting the water quality goals as set forth in the standards. The fact a waterbody does not meet the standards for a particular classification does not mean the waterbody is polluted or of poor quality. Certain types of waterbodies (ie. swamps, lakes, tidal creeks) may naturally have water quality lower than the numeric standards. A waterbody can have water quality conditions below standards due to natural causes and still meet its use classification. A site specific numeric standard may be established by the Department after being subjected to public participation and administrative procedures for adopting regulations. Site specific numeric standards apply only to the stream segment described in the water classification listing, not to tributaries or downstream unspecified waters.

### ***Wetlands***

In the §401 water quality certification process, applications for wetland alterations may be denied or modified due to the special nature of a wetland or the functions that a wetland provides. Wetland impacts must be compensated through restoration, enhancement, preservation, or creation and protected in perpetuity. Future development would be prohibited in these mitigated and legally protected areas. Knowledge of areas that are restricted from development due to mitigation or special water classification is useful in planning future development in a watershed. The list of outstanding resource waters (ORW) has been refined to include wetlands that qualify for, and should be afforded, the highest level of protection. In cooperation with the S.C. Department of Natural Resources's (SCDNR) Division of Land, Water and Conservation, Landsat Thematic Mapper (TM) satellite image data are providing an inventory of wetlands in the basin through the SCDNR's GIS data clearing house for subsequent monitoring and tracking efforts.

### ***Lake Eutrophication Assessment***

The trophic condition of South Carolina lakes is monitored through SCDHEC's network of routine sampling stations and through periodic sampling of additional lakes. All lakes of at least 40 acres in area that offer public access are monitored. Large (major) lakes are those greater than 850 acres in surface area. Minor lakes are those less than 850 acres in surface area.

Beginning with the 1989 statewide lake water quality assessment, a multi-parameter percentile index has been used to quantify overall lake trophic state. The index includes the following trophic condition indicators: water clarity, total phosphorus, total inorganic nitrogen, chlorophyll *a*, and dissolved oxygen. The baseline data for this relative index were collected during the 1980-81 statewide lake water quality assessment. Use of a baseline data set permits trend detection in subsequent assessments. Percentiles for major and minor lakes are derived separately. All data, as well as the programs for deriving index values, are maintained in USEPA's STORET database. A high index value indicates a desirable trophic condition, while low values indicate the need for further study or restoration.

### ***Shellfish Harvesting Waters***

South Carolina's coastal area consists of 579,691 acres of surface water with an assigned classification designated for the harvest of molluscan shellfish. This coastal area is divided into 23 shellfish management areas with a total of 468 monitoring stations. The purpose of this monitoring network is to provide data which accurately reflects the sanitary conditions of coastal shellfish and shellfish growing waters in South Carolina to ensure that the health of shellfish consumers is protected. All shellfish waters receive one of the following harvest classifications:

***Approved*** harvesting status is assigned to waters that are not contaminated with fecal material, pathogenic microorganisms, nor poisonous and deleterious substances in concentrations dangerous to human health. The fecal coliform MPN median or geometric mean should not exceed 14 colonies/100 ml in the water, and 10% of the samples should not exceed 43 colonies/100 ml.

***Conditionally Approved*** harvesting status is assigned to waters that are subject to temporary conditions of actual or potential pollution. Temporary decline in water quality may be caused by activities such as malfunctioning wastewater treatment plants or nonpoint source pollution after rainfall events. Fecal coliform standards in such waters are the same as for the approved classification.

***Restricted*** harvesting status is assigned to waters where a limited degree of pollution renders the shellfish unsafe for direct marketing, but may be marketed after relaying or depuration. The median fecal coliform levels or geometric mean in restricted waters are between 14 and 88 colonies/100 ml, with not more than 10% of the samples exceeding 260 colonies/100 ml.

***Prohibited*** harvesting status is assigned to waters with excessive concentrations of pollutants, or where the potential exists for excessive concentrations. This classification is ascribed to waters where the median fecal coliform MPN or geometric mean exceeds 88 colonies/100 ml, or more than 10% of the samples exceed 260 colonies/100 ml. Shellfish may not be harvested from prohibited areas for human consumption; however, prohibited status does not necessarily indicate lesser water quality, but may indicate a potential for variable water quality due to pollutant sources.

## ***Water Quality Indicators***

Water quality data are used to describe the condition of a waterbody, to help understand why that condition exists, and to provide some clues as to how it may be improved. Water quality indicators include physical, chemical, and biological measurements. Copies of the Standard Operating Procedures used for these measurements are available from the Aquatic Biology Section of the Department's Bureau of Water.

### **MACROINVERTEBRATE COMMUNITY**

Macroinvertebrates are aquatic insects and other aquatic invertebrates associated with the substrates of waterbodies (including, but not limited to streams, rivers, lakes, tidal creeks, and estuaries).

Macroinvertebrates can be useful indicators of water quality because these communities respond to integrated stresses over time which reflect fluctuating environmental conditions. Community responses to various pollutants (e.g. organic, toxic, and sediment) may be assessed through interpretation of diversity, known organism tolerances, and in some cases, relative abundances and feeding types.

### **FISH TISSUE**

Many pollutants occur in such low concentrations in the water column that they are usually below analytical detection limits. Over time many of these chemicals may accumulate in fish tissue to levels that are easily measured. By analyzing fish tissue it is possible to see what pollutants may be present in waterbodies at very low levels. This information can also be used to determine if consumption of the fish pose any undue human health concerns and to calculate consumption rates that are safe.

### **DISSOLVED OXYGEN**

Oxygen is essential for the survival and propagation of aquatic organisms. If the amount of oxygen dissolved in water falls below the minimum requirements for survival, aquatic organisms or their eggs and larvae may die. A severe example is a fish kill. Dissolved oxygen (DO) varies greatly due to natural phenomena, resulting in daily and seasonal cycles. Different forms of pollution also can cause declines in DO.

Changes in DO levels can result from temperature changes or the activity of plants and other organisms present in a waterbody. The natural diurnal (daily) cycle of DO concentration is well documented. Dissolved oxygen concentrations are generally lowest in the morning, climbing throughout the day due to photosynthesis and peaking near dusk, then steadily declining during the hours of darkness.

There is also a seasonal DO cycle in which concentrations are greater in the colder, winter months and lower in the warmer, summer months. Streamflow (in freshwater) is generally lower during the summer and fall, and greatly affects flushing, reaeration, and the extent of saltwater intrusion, all of which affect dissolved oxygen values.

### **BIOCHEMICAL OXYGEN DEMAND**

Five-day biochemical oxygen demand ( $BOD_5$ ) is a measure of the amount of dissolved oxygen consumed by the decomposition of carbonaceous and nitrogenous matter in water over a five-day period. The  $BOD_5$  test indicates the amount of biologically oxidizable carbon and nitrogen that is present in wastewater or

in natural water. Matter containing carbon or nitrogen uses dissolved oxygen from the water as it decomposes, which can result in a dissolved oxygen decline. The quantity of BOD<sub>5</sub> discharged by point sources is limited through the National Pollutant Discharge Elimination System (NPDES) permits issued by the Department. The discharge of BOD<sub>5</sub> from a point source is restricted by the permits so as to maintain the applicable dissolved oxygen standard.

## **pH**

pH is a measure of the hydrogen ion concentration of water, and is used to indicate degree of acidity. The pH scale ranges from 0 to 14 standard units (SU). A pH of 7 is considered neutral, with values less than 7 being acidic, and values greater than 7 being basic.

Low pH values are found in natural waters rich in dissolved organic matter, especially in Coastal Plain swamps and black water rivers. The tannic acid released from the decomposition of vegetation causes the tea coloration of the water and low pH.

High pH values in lakes during warmer months are associated with high phytoplankton (algae) densities. The relationship between phytoplankton and daily pH cycles is well established. Photosynthesis by phytoplankton consumes carbon dioxide during the day, which results in a rise in pH. In the dark, phytoplankton respiration releases carbon dioxide. In productive lakes, carbon dioxide decreases to very low levels, causing the pH to rise to 9-10 SU; hence, excursions of pH beyond Standards may be the result of natural processes. Continuous flushing in streams prevents the development of significant phytoplankton populations and the resultant chemical changes in water quality.

## **FECAL COLIFORM BACTERIA**

Coliform bacteria are present in the digestive tract and feces of all warm-blooded animals, including humans, poultry, livestock, and wild animal species. Fecal coliform bacteria are themselves generally not harmful, but their presence indicates that surface waters may contain pathogenic microbes. Diseases that can be transmitted to humans through water contaminated by improperly treated human or animal waste are the primary concern. At present, it is difficult to distinguish between waters contaminated by animal waste and those contaminated by human waste.

Public health studies have established correlations between fecal coliform numbers in recreational and drinking waters and the risk of adverse health effects. Based on these relationships, the USEPA and SCDHEC have developed enforceable standards for surface waters to protect against adverse health effects from various recreational or drinking water uses. Proper waste disposal or sewage treatment prior to discharge to surface waters minimizes this type of pollution.

## **NUTRIENTS**

Oxygen demanding materials and plant nutrients are the most common substances discharged to the environment by man's activities, through wastewater facilities and by agricultural, residential, and stormwater runoff. The most important plant nutrients, in terms of water quality, are phosphorus and nitrogen. In general, increasing nutrient concentrations are undesirable due to the potential for accelerated growth of aquatic plants, including algae. Nuisance plant growth can create imbalances in the aquatic community, as

well as aesthetic and access issues. High densities of phytoplankton (algae) can cause wide fluctuations in pH and dissolved oxygen. South Carolina has no official standards or criteria for nutrients in water; however, the USEPA has issued recommendations for phosphorus concentrations to prevent over-enrichment.

The forms of nitrogen routinely analyzed at SCDHEC stations are ammonia and ammonium nitrogen ( $\text{NH}_3/\text{NH}_4$ ), total Kjeldahl nitrogen (TKN), and nitrite and nitrate nitrogen ( $\text{NO}_2/\text{NO}_3$ ). Ammonia and ammonium are readily used by plants. TKN is a measure of organic nitrogen and ammonia in a sample. Nitrate is the product of aerobic transformation of ammonia, and is the most common form used by aquatic plants. Nitrite is usually not present in significant amounts.

Total phosphorus (TP) is commonly measured to determine phosphorus concentrations in surface waters. TP includes all of the various forms of phosphorus (organic, inorganic, dissolved, and particulate) present in a sample.

#### **TURBIDITY**

Turbidity is an expression of the scattering and absorption of light through water. The presence of clay, silt, fine organic and inorganic matter, soluble colored organic compounds, and plankton and other microscopic organisms increases turbidity. Increasing turbidity can be an indication of increased runoff from land. It is an important consideration for drinking water as finished water has turbidity limits.

#### **TOTAL SUSPENDED SOLIDS**

Total Suspended Solids (TSS) are the suspended organic and inorganic particulate matter in water. Although increasing TSS can also be an indication of increased runoff from land, TSS differs from turbidity in that it is a measure of the mass of material in, rather than light transmittance through, a water sample. High TSS can adversely impact fish and fish food populations and damage invertebrate populations. There are no explicit state standards for TSS.

#### **HEAVY METALS**

Concentrations of cadmium, chromium, copper, lead, mercury, nickel, and zinc in water are routinely measured by the Department to compare to State standards intended to protect aquatic life and human health. These metals occur naturally in the environment, and many are essential trace elements for plants and animals. Human activities, such as land use changes and industrial and agricultural processes, have resulted in an increased flux of metals from land to water. Atmospheric inputs are recognized as important sources of metals to aquatic systems. Metals are released to the atmosphere from the burning of fossil fuels (coal, oil, gasoline), wastes (medical, industrial, municipal), and organic materials. The metals are then deposited on land and in waterways from the atmosphere via rainfall.



## ***Assessment Methodology***

The Watershed Water Quality Assessment is a geographically-based document that describes, at the watershed level, water quality as well as conditions and activities related to water quality. This section provides an explanation of the information assessment methodology used to generate the watershed-level summaries. Water quality data used in this assessment are presented in Appendix B.

### **USE SUPPORT DETERMINATION**

At the majority of SCDHEC's surface water monitoring stations, samples for analysis are collected as surface grabs once per month, quarter, or year, depending on the parameter. Grab samples collected at a depth of 0.3 meters are considered surface measurements, and are used to establish representative physical conditions and chemical concentrations in the waterbodies sampled. At most stations sampled by boat, dissolved oxygen and temperature are sampled as a water column profile, with measurements being made at a depth of 0.3 meters below the water surface and at one-meter intervals to the bottom. At stations sampled from bridges, these parameters are measured only at a depth of 0.3 meters. All water and sediment samples are collected and analyzed according to standard procedures. Macroinvertebrate community structure is analyzed routinely at selected stations as a means of detecting adverse biological impacts on the aquatic fauna due to water quality conditions which may not be readily detectable in the water column chemistry.

For the purpose of assessment, only results from surface samples are used in water quality standards comparisons and trend assessments. This information is considered to represent "average" conditions, as opposed to extremes, because of the inability to target individual high or low flow events on a statewide basis. The more extreme instream chemical concentrations resulting from nonpoint source inputs from rain events or point source inputs of a variable nature are frequently missed because routine monthly sampling rarely coincides with the time of release. Results from water quality samples can be compared to state standards and USEPA criteria, with some restrictions due to time of collection and sampling frequency. The monthly sampling frequency employed in the ambient monitoring network may be insufficient for strict interpretation of standards. The USEPA does not define the sampling method or frequency other than indicating that it should be "representative". A grab sample is considered to be representative for indicating excursions relative to standards: a single grab sample is more representative of a one-hour average than a four-day average, more representative of a one-day average than a one-month average, and so on (see also Screening & Additional Considerations for Water Column Metals below). When the sampling method or frequency does not agree with the intent of the particular standard, conclusions about water quality should be considered as only an indication of conditions.

The time period used to assess standards compliance is the most recent complete five years of data, which for the Edisto River Basin is 1993 through 1997.

### **AQUATIC LIFE USE SUPPORT**

One important goal of the Clean Water Act and state standards is to maintain the quality of surface waters in order to provide for the survival and propagation of a balanced indigenous aquatic community of fauna and flora. The degree to which aquatic life is protected (aquatic life use support) is assessed by comparing important water quality characteristics and the concentrations of potentially toxic pollutants with standards. Support of aquatic life uses is based on the percentage of standards excursions and, where data are available, the composition and functional integrity of the biological community. For lakes, support of aquatic life uses is also evaluated using a measure of trophic state. A number of waterbodies have been given specific standards for pH and dissolved oxygen, which reflect natural conditions.

A dissolved oxygen (DO) criterion of not less than 4 mg/l is used for Class SB, a criterion of not less than 6 mg/l is used for TN and TPGT, and a daily average not less than 5 mg/l with a low of 4 mg/l is used for all other Classes. An excursion is an occurrence of a DO concentration less than the stated criterion. For pH, there are several acceptable ranges applied depending on the Class of water: 6-8 SU for TPGT; 6-8.5 SU for FW; 5-8.5 SU for FW\*; and 6.5-8.5 for SFH, SA, and SB. For DO and pH, if 10 percent or less of the samples contravene the appropriate standard, then aquatic life uses are said to be fully supported. A percentage of standards excursions between 11-25 is considered partial support, and a percentage greater than 25 is considered to represent nonsupport, unless excursions are due to natural conditions. Dissolved oxygen and pH may vary from the ranges specified in the standards due to a variety of natural causes.

When comparing SCDHEC data to DO standards, it is necessary to consider sampling bias due to season or tide stage. Samples are collected as a single instantaneous grab sample, which is not truly representative of the daily average used as the criterion for most classifications. Secondary stations are sampled only during summer months and generally experience a higher rate of DO excursions as a result. It is essential to examine the data to ascertain such patterns of excursions before summarily concluding that the indicated violations constitute poor water quality.

For any individual toxicant (heavy metals, priority pollutants, chlorine, ammonia), if the acute aquatic life standard is exceeded in more than 10 percent of the samples, based on at least ten samples, aquatic life uses are not supported. If the acute aquatic life standard is exceeded more than once, but in less than or equal to 10 percent of the samples, uses are partially supported. If fewer than ten samples were collected, discretion must be used and other factors considered, such as the magnitude of the excursions or number of toxicants with excursions. In such a circumstance it is noted that aquatic life uses may not be fully supported and the site is prioritized for the collection of biological data, or additional monitoring and investigation, to verify the true situation.

Biological data are the ultimate deciding factor for aquatic life uses, regardless of chemical conditions. The goal of the standards is the protection of a balanced indigenous aquatic community.

#### **MACROINVERTEBRATE DATA INTERPRETATION**

Macroinvertebrate community assessments are used, where available, to supplement or verify Aquatic Life Use Support determinations and to evaluate potential impacts from the presence of sediment

contaminants. Aquatic and semi-aquatic macroinvertebrates are identified to the lowest practical taxonomic level depending on the condition and maturity of specimens collected. The EPT Index and the North Carolina Biotic Index are the main indices used in analyzing macroinvertebrate data. To a lesser extent, taxa richness and total abundance may be used to help interpret data. The EPT Index or the Ephemeroptera (mayflies) - Plecoptera (stoneflies) - Trichoptera (caddisflies) Index is the total taxa richness of these three generally pollution-sensitive orders. EPT values are compared with least impacted regional sites. The biotic index for a sample is the average pollution tolerance of all organisms collected, based on assigned taxonomic tolerance values. A database is currently being developed to establish significant EPT index levels to be used in conjunction with the biotic index to address aquatic life use support.

Taxa richness is the number of distinct taxa collected and is the simplest measure of diversity. High taxa richness is generally associated with high water quality. Increasing levels of pollution progressively eliminate the more sensitive taxa, resulting in lower taxa richness. Total abundance is the enumeration of all macroinvertebrates collected at a sampling location. This is generally not regarded as a qualitative metric. However, when gross differences in abundance occur between stations this metric may be considered as a potential indicator.

#### **RECREATIONAL USE SUPPORT**

The degree to which the swimmable goal of the Clean Water Act is attained (recreational use support) is based on the frequency of fecal coliform bacteria excursions, defined as greater than 400/100 ml for all surface water classes. Comparisons to the bacteria geometric mean standard are not considered appropriate based on sampling frequency and the intent of the standard. If 10 percent or less of the samples are greater than 400/100 ml then recreational uses are said to be fully supported. A percentage of standards excursions between 11-25% is considered partial support of recreational uses, and greater than 25% is considered to represent nonsupport of recreational uses.

#### **FISH CONSUMPTION USE SUPPORT**

The Department uses a risk-based approach to evaluate mercury concentrations in fish tissue and to issue consumption advisories in affected waterbodies. This approach contrasts the average daily exposure dose to the reference dose (RfD). Using these relationships, fish tissue data are interpreted by determining the consumption rates that would not be likely to pose a health threat to adult males and nonpregnant adult females. Because an acceptable RfD for developmental neurotoxicity has not been developed, pregnant women, infants, and children were advised to avoid consumption of fish from any waterbody where an advisory was issued.

Fish consumption use support is determined by the occurrence of advisories or bans on consumption for a waterbody. For the support of fish consumption uses, a fish consumption advisory indicates partial use support, a consumption ban indicates nonsupport of uses.

## **HUMAN HEALTH STANDARDS**

State standards for human health are also evaluated in the preparation of the Watershed Water Quality Assessments. For contaminants with human health standards (ie. heavy metals, pesticides), a potential human health threat is indicated if the median concentration exceeds the standard.

### ***Additional Screening and Prioritization Tools***

Evaluation of water quality data and other supplemental information facilitates watershed planning. Information from the following sources is used to develop watershed-based protection and prevention strategies.

## **LONG-TERM TREND ASSESSMENT**

As part of the watershed assessments, surface data from each station are analyzed for statistically significant long-term trends using a modification of Kendall's tau, which is a nonparametric test removing seasonal effects. Flows are not available for most stations, and the parametric concentrations are not flow-corrected. Seasonal Kendall's tau analysis is used to test for the presence of a statistically significant trend of a parameter, either increasing or decreasing, usually over a twelve to fifteen year period. It indicates whether the concentration of a given parameter is exhibiting consistent change in one direction over the specified time period. A two sided test at  $p = 0.1$  is used to determine statistically significant trends, and the direction of trend. An estimate of the magnitude of any statistically significant trend is calculated.

A rigorous evaluation for trends in time-series data usually includes a test for autocorrelation. The data are not tested for autocorrelation prior to the trend analysis. It is felt that autocorrelation would not seriously compromise a general characterization of water quality trends based on such a long series of deseasonalized monthly samples.

One of the advantages of the seasonal Kendall test is that values reported as being below detection limits (DL) are valid data points in this nonparametric procedure, since they are all considered to be tied at the DL value. When the DL changed during the period of interest, all values are considered to be tied at the highest DL occurring during that period. Since it is possible to measure concentrations equal to the value of the DL, values less than DL are reduced by subtraction of a constant so that they remain tied with each other, but are less than the values equal to the DL. Since fecal coliform bacteria detection limits vary with sample dilution, there is no set DL; therefore, for values reported as less than some number, the value of the number is used.

## **SEDIMENT SCREENING**

There are no sediment standards; therefore, in order to identify sediments with elevated metals concentrations, percentiles are constructed using five years of statewide sediment data. Only values greater than the detection limit were used for chromium, copper, nickel, lead, and zinc. Because so few concentrations of cadmium and mercury are measured above the detection limit, all samples were pooled for

these metals. A sediment metal concentration is considered to be high if it is in the top 10% of the pooled results, and very high if it is in the top 5%. Any analytical result above detection limits is flagged for pesticides, PCBs, and other priority pollutants. Sites with noted high metals concentrations or the occurrence of other contaminants above detection limits are prioritized for the collection of biological data, or additional monitoring and investigation, to verify the true situation.

#### **WATER COLUMN METALS ANALYSES**

The USEPA criteria for heavy metals to protect aquatic life are specified as a four-day average and a one-hour average, and have been adopted as state standards. Because of the quarterly sampling frequency for heavy metals, the USEPA advises against comparisons to chronic toxicity standards (four-day average concentration); therefore, only the acute standard (one-hour average) for the protection of aquatic life is used in the water quality assessment (Table 1).

Zinc and copper are elevated in surface waters statewide and concentrations are frequently measured in excess of the calculated acute aquatic life standards. To identify areas where zinc, copper, and other metals are elevated in the water column above normal background concentrations, concentrations greater than the detection limit from all SCDHEC monitoring sites statewide for a five year period are pooled and the 90th and 95th percentiles are computed. This is done separately for each metal for both fresh and saltwaters. The individual measurements from each monitoring station are then compared to these percentiles, as well as to state standards. As in sediments, a metal concentration is referred to as "high" if it is in the top 10% of the pooled results, and "very high" if it is in the top 5%. All water column values referred to as "high" or "very high" are also in excess of the acute aquatic life standard listed in Table 1. For chromium, because so few concentrations are above the detection limit, all samples collected are used to generate the percentiles. Sites with high metals concentrations are prioritized for the collection of biological data, or additional monitoring and investigation, to verify the true situation.

Table 1. Metal Standards in Water (µg/l)				
Metal	Present Detection Level	Freshwater 1Hr. Acute Ave.	Saltwater 1Hr. Acute Ave.	Human Health
*Cadmium	10.0	1.79	43.0	5.000
Chromium (VI)	10.0	16.00	1100.0	50.000
*Copper	10.0	9.22	2.9	
*Lead	50.0	33.78	140.0	50.000
Mercury	0.2	2.40	2.1	0.153
*Nickel	20.0	789.00	75.0	4584.000
*Zinc	10.0	65.00	95.0	
* Freshwater standards based on a hardness of 50 mg/l as CaCO <sub>3</sub> .				

The analytical procedures used by the Department yield total metal concentration, which is a relatively conservative measure, since the total metal concentration is always greater than the acid-soluble or dissolved fraction. Most heavy metal criteria for freshwater are calculated from formulas using water hardness. The formulas used to calculate criteria values are constructed to apply to the entire United States, including Alaska and Hawaii. As with all the USEPA criteria, there is also a large margin of safety built into the calculations. The applicability of the hardness-based criteria derived from the USEPA formulas to South Carolina waters has been a subject of much discussion. Hardness values vary greatly nationwide (from zero into the hundreds), with South Carolina representing the lower end of the range (statewide average value is approximately 20 mg/l). Representatives of the USEPA Region IV standards group have stated that no toxicity data for hardness values less than 50 mg/l were used in the development of the formulas. They have expressed reservations about the validity of the formulas when applied to hardness values below 50 mg/l. Based on this opinion, South Carolina's State standards for metals are based on a hardness of 50 mg/l for waters where hardness is 50 mg/l or less, resulting in several criteria values below the Department's current analytical detection limits. Therefore, any detectable concentration of cadmium, copper, or lead is an excursion beyond recommended criteria.

The SCDHEC monitoring data have historically indicated that zinc and copper levels in South Carolina waters are elevated relative to USEPA criteria, apparently a statewide phenomenon in both fresh and salt waters, and possibly resulting from natural conditions, nonpoint sources, or airborne deposition. These levels do not appear to adversely affect state fisheries, which suggests that the levels are the result of long-term local conditions to which the fauna have adapted, as opposed to point source pollution events. It is difficult to assess the significance of heavy metal excursions due to the questionable applicability of the formulas at low hardness values and calculated criteria below present detection limits.

## **Point Source Contributions**

### ***Wasteload Allocation Process***

A wasteload allocation (WLA) is the portion of a stream's assimilative capacity for a particular pollutant which is allocated to an existing or proposed point source discharge. Existing WLAs are updated during the basin review process and included in permits during the normal permit expiration and reissuance process. New WLAs are developed for proposed projects seeking a discharge permit or for existing discharges proposing to increase their effluent loading at the time of application. Wasteload allocations for oxygen demanding parameters are developed by the Water Quality Modeling Section, and WLAs for toxic pollutants and metals are developed by the appropriate permitting division.

The ability of a stream to assimilate a particular pollutant is directly related to its physical and chemical characteristics. Various techniques are used to estimate this capacity. Simple mass balance/dilution calculations may be used for a particular conservative (nondecaying) pollutant while complex models may be used to determine the fate of nonconservative pollutants that degrade in the environment. Waste characteristics, available dilution, and the number of discharges in an area may, along with existing water quality, dictate the use of a simple or complex method of analysis. Projects which generally do not require complex modeling include: groundwater remediation, noncontact cooling water, mine dewatering, air washers, and filter backwash.

Streams are designated either effluent limited or water quality limited based on the level of treatment required of the dischargers to that particular portion of the stream. In cases where the USEPA published effluent guidelines and the minimum treatment levels required by law are sufficient to maintain instream water quality standards, the stream is said to be effluent limited. Streams lacking the assimilative capacity for a discharge at minimum treatment levels are said to be water quality limited. In cases where better than technology limits are required, water quality, not minimum requirements, controls the permit limits. The Department's Water Quality Modelling Section recommends limits for numerous parameters including ammonia nitrogen (NH<sub>3</sub>-N), dissolved oxygen (DO), total residual chlorine (TRC), and five-day biochemical oxygen demand (BOD<sub>5</sub>). Limits for other parameters, including metals, toxics, and nutrients are developed by the Water Facilities Permitting Division or the Industrial, Agricultural, and Stormwater Permitting Division in conjunction with support groups within the Department.

### ***Permitting***

The Water Facilities Permitting Division and the Industrial, Agricultural, and Stormwater Permitting Division are responsible for drafting and issuing National Pollutant Discharge Elimination System (NPDES) permits. Facilities are defined as either "major" or "minor". For municipal permits, a facility is considered a "major" if it has a permitted flow of 1 MGD or more and is not a private facility. The determination for industrial facilities is based on facility and stream characteristics, including toxicity, amount of flow, load of oxygen, proximity of drinking water source, potential to exceed stream standards, and potential effect on coastal waters.

A completed draft permit is sent to the permittee, the SCDHEC District office, and if it is a major permit, to the USEPA for review. When the permit draft is finalized, a public notice is issued. Comments from the public are considered and, if requested, a public hearing may be arranged. Both oral and written

comments are collected at the hearing, and after considering all information, the Department staff make the decision whether to issue the permit as drafted, issue a modified permit, or to deny the permit. Everyone who participated in the process receives a notice of the final decision. A copy of the final permit will be sent to anyone who requests a it. It is anticipated that minor permits will be grouped by watershed and publicly noticed together; major permits will individually stand public review. Staff decisions may be appealed according to the procedures in R.61-72.

The permitting Divisions use general permits with statewide coverage for certain categories of minor NPDES permits. Discharges covered under general permits include utility water, potable surface water treatment plants, potable groundwater treatment plants with iron removal, petroleum contaminated groundwater, and mine dewatering activities. Additional activities proposed for general permits include bulk oil terminals, aquacultural facilities, and ready-mix concrete/concrete products. Land application systems for land disposal and lagoons are also permitted.

## **Nonpoint Source Contributions**

Nonpoint source pollutants are generally introduced to a waterbody during a storm event and enter the system from diverse areas. Nonpoint source contributions originate from a variety of activities that include agriculture, silviculture, construction, urban stormwater runoff, hydrologic modification, landfills, mining, and residual wastes.

Section 319 of the 1987 Amendments to the Clean Water Act required states to assess the nonpoint source water pollution associated with surface and groundwater within their borders and then develop and implement a management strategy to control and abate the pollution. The first Assessment of Nonpoint Source Pollution in South Carolina accomplished this purpose. The NPS Management Program developed strategies and targeted waterbodies for priority implementation of management projects. The priority list has been updated several times since then. The current list appears in the State Nonpoint Source Pollution Management Program. Comprehensive projects are currently being implemented in a number of these watersheds. Components of the projects vary depending on the particular NPS impacts in the watershed, but all include BMP demonstrations, education, and monitoring.

Section 6217 of the 1990 Coastal Zone Act Reauthorization Amendments (CZARA) requires states with federally approved Coastal Zone Management Programs to develop Coastal Nonpoint Source Pollution Control Programs. At the federal level, the program is administered and funded jointly by the National Oceanic and Atmospheric Administration (NOAA) and EPA. In South Carolina, the Department's Office of Ocean and Coastal Resource Management and the Bureau of Water are responsible for development and implementation of the program. The Department submitted a State Nonpoint Source Pollution Management Program in October 1995, which satisfies the requirements of §6217 and §319.

The purpose of South Carolina's Nonpoint Source Pollution Management Program is to insure the protection and restoration of the state's waters from nonpoint source water pollution impacts. The Plan document describes programs (both regulatory and voluntary) for NPS abatement, targets watersheds for NPS project implementation, and describes the state's strategy under each of the eight categories of NPS sources identified in South Carolina. In each of the categorical sections, management measures are described. Management measures are defined as "economically achievable measures for the control of the addition of



pollutants from existing and new categories and classes of nonpoint sources of pollution". The management measures address the following major categories: agriculture, forestry, urban areas, marinas/recreational boating, hydromodification, mining, land application of wastes, and wetlands.

### **Landfill Activities**

All landfill activities within the State are permitted and regulated by the Department's Bureau of Land and Waste Management. All active and closed industrial and municipal solid waste landfills are identified in the appropriate watershed evaluations.

### **Mining Activities**

Mining activities within the State are permitted by the Mining and Reclamation Division of the Department's Bureau of Land and Waste Management. Soil excavation activities and locations are identified in the appropriate watershed evaluations.

### **Camping Facilities**

The types of camping facilities permitted by the Department through R.61-39 are Resident Camps and Family Camps. Resident camps are organized camps where one or more buildings are provided for sleeping quarters. These camps are typically operated for educational, recreational, religious, or health purposes. Family camps are organized camps where camp sites are provided for use by the general public or certain groups. The camp sewage is discharged into a public collection, treatment and disposal system if available, or an onsite wastewater treatment and disposal system (septic tank) is used. Camp locations are identified in the appropriate watershed evaluations.

### **Groundwater Concerns**

Groundwater is an important resource for drinking water use, together with agricultural, industrial and commercial usages. Based on USEPA drinking water standards, the overall quality of South Carolina's groundwater is excellent. Contaminated groundwater is expensive and difficult to restore; therefore, groundwater protection for present and future usage is the management emphasis. Localized sources of groundwater contamination can include: septic tanks, landfills (municipal and industrial), surface impoundments, oil and gas brine pits, underground storage tanks, above ground storage tanks, injection wells, hazardous waste sites (abandoned and regulated), salt water intrusion, land application or treatment, agricultural activities, road salting, spills and leaks. For the purposes of this assessment, only groundwater contamination affecting surface waters will be identified. The SCDHEC groundwater contamination inventory was used to identify groundwater-related problem areas in the basin. Sites in the inventory are referenced by name and county, and are updated annually.

## **Water Supply**

Water treatment facilities are permitted by the Department for municipal and industrial potable water production. As per the 1983 Water Use Reporting and Coordination Act (Act 282), all water uses over 100,000 gallons per day must report their usage. This includes industrial, agricultural, mining, golf courses, public supply, commercial, recreational, hydro power, thermo power, and nuclear power activities. Intake location and the volume removed from a stream are identified in the watershed evaluations for both municipal (potable) and industrial uses.

## **Growth Potential and Planning**

Land use and management can define the impacts to water quality in relation to point and nonpoint sources. Assessing the potential for an area to expand and grow allows for water quality planning to occur and, if appropriate, increased monitoring for potential impairment of water quality. Indicators used to predict growth potential include water and sewer service, road and highway accessibility, and population trends. These indicators and others were used as tools to determine areas within the Edisto River Basin having the greatest potential for impacts to water quality as a result of development.

Many counties in the Edisto Basin lack county wide zoning ordinances; therefore, there is little local regulatory power to influence the direction or magnitude of regional growth. The majority of municipalities have zoning ordinances in place; however, much of the growth takes place just outside the municipal boundaries, where infrastructure is inadequate. Section 208 of the Clean Water Act serves to encourage and facilitate the development and implementation of areawide waste treatment management plans. The §208 Areawide Water Quality Management Plans were completed in great detail during the 1970's and have recently been updated. Information from the updated reports are used in the individual watershed evaluations.

Watershed boundaries extend along topographic ridges and drain surrounding surface waters. Roads are commonly built along ridge tops, with the best drainage conditions. Cities often develop in proximity to ridges as a result of their plateau terrain. It is not uncommon, then, to find cities or road corridors located along watershed boundaries, and thus influencing or impacting several watersheds.

## **Watershed Stewardship Programs**

Public participation is an important component of the Department's Watershed Water Quality Management Program. For the Edisto Basin, workshops were held in the City of Orangeburg and the Town of Lexington during the assessment development to gain a better understanding of the watershed residents' concerns. Additional benefits to this interaction on the local level include improved public awareness about SCDHEC water programs, and increased local interest and participation in water quality improvement. The meetings are summarized in Appendix A. Described below are some of the Department's water programs that encourage public interest and involvement in water quality.

### **Source Water Assessment Program**

A safe, adequate source of drinking water is key to development of communities and the health of citizens. The Safe Drinking Water Act (SDWA) provides authority to protect sources of drinking water. As a result of the 1996 amendments to the SDWA, source water protection has become a national priority. States are required to develop a plan for assessment of source waters for all federally defined public groundwater and surface water systems.

The Source Water Assessment Program (SWAP) involves determining the boundaries of the areas that are the source of waters for public water systems. For groundwater systems, these areas are defined using groundwater flow models. For surface water systems, the 14-digit Hydrologic Unit Code watershed is the designated protection area (although certain areas within the basin will be segmented as being of greater vulnerability to contamination from overland flow, groundwater contributions to surface water, and direct spills into the surface water). Known and potential sources of contamination in the delineated area must be identified, and the inventoried sources evaluated to determine the susceptibility of public water systems to such contaminants. Assessments must be made available to the public.

Local involvement will be a critical factor in the success of the SWAP, and local government, citizen groups, environmental groups, water suppliers, and the Department must all work together to increase the general public's awareness of where drinking water comes from and how to better protect sources of drinking water. Implementation of source water protection activities will also occur at the local level, and local authorities may wish to base zoning and land-use planning on the source water assessments. The SWAP will be a key part of the Department's watershed management approach. To avoid duplication, information gathered from existing regulatory programs and/or watershed protection efforts will be utilized (e.g., ambient monitoring programs, TMDLs, etc.).

### **South Carolina Water Watch**

South Carolina Water Watch is a unique effort to involve the public and local communities in water quality protection. The Water Watch program was developed to encourage South Carolina's citizens to become stewards of the state's lakes, rivers, streams, estuaries, and wetlands. Volunteers select a water resource on which to focus and perform activities aimed at protecting water quality, such as shoreline surveys, public education, and litter cleanups. The Water Watch coordinator assists participants with materials and

training to help make projects successful. SCDHEC invites individuals, school groups, civic organizations, businesses, and local governments to learn about and protect the quality of our waterways by contacting the Water Watch coordinator at 803-898-4300.

## **Champions of the Environment**

Champions of the Environment is a student recognition program that raises awareness of environmental issues. Nationally recognized for its innovative approach to environmental education, the program promotes hands-on learning by recognizing students working on exemplary environmental projects beyond the realm of the classroom. With scholarships and media coverage, Champions of the Environment encourages student initiative and self-esteem. The program promotes environmental awareness, leadership, conservation, creativity, and self-confidence through activities such as group projects, public speaking, and environmental research. Champions of the Environment is jointly sponsored by Dupont, Union Camp, WIS-TV, and SCDHEC. For more information contact the Champions of the Environment coordinator at 803-898-4300.

## **Clean Water State Revolving Fund**

Congress created the Clean Water State Revolving Fund (SRF) in 1987, to replace the \$201 Construction Grants program. In doing so, 'state banks' were created to lend money for virtually any type of water pollution control infrastructure project. Project types include construction of wastewater treatment systems, nonpoint source pollution control, wetlands and estuary protection, and other watershed projects. The interest rate on the loans is always below the current market rate. As repayments are made on the loans, funds are recycled to fund additional water protection projects. Approximately \$3 billion is available annually on the national level for SRF. South Carolina has approximately \$16.5 million available for loans in 1998. The vast majority of the SRF funds have been used for the construction of traditional municipal wastewater treatment systems. Because of its inherent flexibility, the SRF program is well suited to accommodate the watershed approach.

SRF loans are available to units of state, local, and regional government, and special purpose districts. South Carolina law prevents loans from being made directly to private organizations and individuals; however, it is possible for governmental entities to be the SRF recipient and in turn loan the funds to private concerns and individuals. Local governments such as cities and counties and other units of government such as Soil and Water Conservation Districts, Councils of Government, and Water and Sewer Districts are encouraged to apply for SRF loans for nonpoint source projects. Nonpoint source projects may include construction and maintenance of stormwater management facilities, establishment of a stormwater utility, purchase of land for wetlands and riparian zones, and implementation of source water protection assessments. For more information contact the State Revolving Fund coordinator at 803-898-4300.

## **Watershed Protection and Restoration Strategies**

SCDHEC's Bureau of Water is responsible for ensuring that South Carolina's water is safe for drinking and recreation, and suitable to support aquatic life. This section provides an overview of other important Bureau programs and strategies applied statewide to protect and restore water quality. The point and nonpoint source controls described previously assist with achieving these goals.

Under section 303(d) of the Federal Clean Water Act, each state is required to provide a comprehensive inventory of impaired waters for which existing required pollution controls are not stringent enough to achieve State water quality standards or Federal Clean Water Act goals. This biennial list, commonly referred to as the "303(d) list" is the basis for targeting waterbodies for watershed-based solutions. A copy of the current 303(d) list can be obtained by contacting the Bureau of Water. Several Bureau programs address these impaired streams in an effort to restore them.

### **Total Maximum Daily Load**

A Total Maximum Daily Load (TMDL) is the calculated maximum allowable pollutant loading to a waterbody at which water quality standards are maintained. A TMDL is made up of two main components, a load allocation and a wasteload allocation. A load allocation is the portion of the receiving water's loading capacity attributed to existing or future nonpoint sources or to natural background sources. The waste load allocation is the portion of a receiving water's loading capacity allocated to an existing or future point source.

A TMDL is a means for recommending controls needed to meet water quality standards in a particular water or watershed. Historically, the typical TMDL has been developed as a wasteload allocation, considering a particular waterbody segment, for a particular point source, to support setting effluent limitations. In order to address the combined cumulative impacts of all sources, broad watershed-based TMDLs are now being developed.

The TMDL process is linked to all other State water quality activities. Water quality impairments are identified through monitoring and assessment. Watershed-based investigations result in source identification and TMDL development. TMDLs form links between water quality standards and point and nonpoint source controls. Where TMDLs are established, they constitute the basis for NPDES permits and for strategies to reduce nonpoint source pollution. The effectiveness and adequacy of applied controls are evaluated through continued monitoring and assessment.

### **Antidegradation Implementation**

The State's Antidegradation Policy as part of S.C. Regulation 61-68 is represented by a three-tiered approach to maintaining and protecting various levels of water quality and uses; streams included on the 303(d) list are addressed under Tier 1. Tier 1 antidegradation policies apply to all waters of the State and require that existing uses and the minimum level of water quality for those uses be maintained and protected. Tier 2 policies apply to high water quality where the water quality exceeds the mandatory minimum levels to support Clean Water Act's goals of propagation of fish, shellfish, wildlife, and recreation in and on the water. The Department considers all the waters of the State as high quality waters. Tier 3 policies apply to the

maintenance of water quality in waters which constitute an Outstanding National Resource Water and do not allow for any permanent permitted dischargers. Outstanding Resource Waters of the State are provided a higher level of protection than Tier 2, but do not meet the requirements of Tier 3.

The antidegradation rules will be implemented for Tier 1 protection when applying narrative standards included in Regulation 61-68 as follows: if nutrient loadings caused a waterbody to be included on the 303(d) list, then the Department will not allow a permitted net increase of loading for the appropriate nutrient(s) until such time as a TMDL is developed for the waterbody. In addition, Tier 1 protection will be implemented when applying numeric standards included in Regulation 61-68 for human health, aquatic life, and organoleptic protection as follows: if a waterbody has been affected by a parameter of concern causing it to be on the 303(d) list, then the Department will not allow a permitted net increase of loading for the parameter of concern unless the concentration will not contribute to a violation of water quality standards. Maintenance of current levels will be achieved by reallocation of existing total loads or by meeting applicable water quality standards at the end-of-pipe. No discharge will be allowed to cause or contribute to further degradation of a 303(d) listed waterbody. This no net increase will be achieved by reallocation of existing total load(s) or by meeting applicable water quality standard(s) at the end-of-pipe.

#### **401 Water Quality Certification Program**

If a Federal permit for a discharge into waters of the State, including wetlands, is required, the Department must issue Water Quality Certification pursuant to Section 401 of the Federal Clean Water Act. Certification is required for permits issued by the U.S. Army Corps of Engineers for construction in navigable waters and for deposition of dredged or fill material.

Regulation 61-101 presents administrative and technical guidance for the water quality certification program and requires DHEC to consider whether or not a project is water dependent; whether or not there are feasible alternatives which will have less adverse consequences on water quality and classified uses; the intended purpose of the project; and all potential water quality impacts of the project, both direct and indirect, over the life of the project. Any project with the potential to affect waters of the State must be conducted in such a manner to maintain the specified standards and classified and existing water uses.

As a routine part of the 401 Water Quality Certification review process, the waterbody in question is identified as impaired or not impaired according to the 303(d) list. If it is impaired, the parameter of concern is noted, along with any steps required to prevent further degradation of the water quality of that waterbody. In an effort to facilitate watershed restoration where appropriate, mitigation for unavoidable wetland impacts is encouraged in areas that improve 303(d) listed waters.

#### **Stormwater Program**

Stormwater discharges result from precipitation during rain events. Runoff washes pollutants associated with industrial activities (including construction activity), agricultural operations, and commercial

and household sites directly into streams, or indirectly into drainage systems that eventually drain into streams. The SCDHEC Stormwater Permitting Program focuses on pollution prevention to reduce or eliminate stormwater pollution. The Department has general permitting authority for stormwater discharges associated with industrial activity, including construction. General permits SCR000000 and SCR100000 for industrial and construction activities, respectively, require permittees to develop and implement stormwater pollution prevention plans that establish best management practices to effectively reduce or eliminate the discharge of pollutants via stormwater runoff. The Stormwater and Agricultural Permitting Section is responsible for issuing NPDES storm water permits to prevent degradation of water quality as well as for issuing sediment and erosion control permits for construction sites. SCDHEC's Bureau of Ocean and Coastal Resource Management manages the State sediment and erosion control in the coastal area.

Regulation 61-9 requires a compilation of all existing State water quality data with STORET data being used as a baseline. If analysis indicates a decrease in water quality then corrective measures must be taken. The permittee will identify all impaired water bodies in a Stormwater Management Plan (SWMP). In addition, existing pollution discharge control methods will be identified and incorporated into the SWMP. Procedures, processes and methods to control the discharge of pollutants from the municipal separate storm sewer system (MS4) into impaired water bodies and publicly owned lakes included on the 303(d) list will be described in the SWMP. The effectiveness of these controls will be assessed and necessary corrective measures, if any, shall be developed and implemented.

### **South Carolina Animal Feeding Operations Strategy**

Among the general categories of pollution sources, agriculture ranks as the number one cause of stream and lake impairment nationwide. Many diseases can potentially be contracted from drinking water or coming into contact with waters contaminated with animal wastes. The Department has recently published SC Regulation 61-43: *Standards for the Permitting of Agricultural Animal Facilities* to address the permitting of animal feeding operations (AFOs) and updated Regulation 61-9: *Water Pollution Control Permits* to address concentrated animal feeding operations (CAFOs). Implementing these regulations and their corresponding compliance efforts are a priority for the Department in order to reduce public health and environmental impacts from AFOs. There are currently no CAFOs in operation in South Carolina, and approximately 2,000 AFOs. Using the Watershed Program cycle and the division of the state into five regions, AFOs will be monitored and inspected by region. The 303(d) list will be used to prioritize the inspections. After all the inspections have been made in a region, the Department will move on the next sub-basin grouping in the watershed cycle. The Department is continuing to work in cooperation and coordination with the US Department of Agriculture, the Natural Resources Conservation Service, the South Carolina Department of Agriculture, the South Carolina Soil and Water Conservation Districts, and the Clemson Extension Service.

### **Sanitary Sewer Overflow Strategy**

Sanitary sewers are designed to collect municipal and industrial wastewater, with the allowance for some acceptable level of infiltration and infow, and transport these flows to a treatment facility. When the sewer system is unable to carry these flows, the system becomes surcharged and an overflow will occur.

Sanitary sewer overflows (SSOs) have existed since the introduction of separate sanitary sewers, and most are caused by inadequate operation, maintenance, and management of the collection system.

The SSO strategy addresses compliance and enforcement efforts by the Department to ensure compliance by publicly/private owned treatment plants (PPOTWs) with the requirements of the statutes and their NPDES and ND permits. The Department has initiated a Sanitary Sewer Overflow Compliance and Enforcement Strategy to shift resources historically applied to treatment plant inspections to include evaluations of pump stations and collection systems. To assist evaluators in selecting candidate systems, staff will utilize the 303(d) list of impaired waters to identify waters impacted by fecal coliform or other appropriate pollutants and correlate those with collection systems with incidences of SSOs. The Department's Enforcement Referral Procedures Document will be used to determine when a PPOTW should be referred to enforcement for SSOs. The enforcement process allows for the Department to consider actions taken by the PPOTW such as: timely and proper notification, containment and mitigation of discharge, voluntarily conducting self evaluations, and requests for compliance assistance. The Department will take immediate action where it has been determined that SSOs have occurred and the PPOTW has not made timely and proper notification.

### **Referral Strategy for Effluent Violations**

The Department has developed referral effluent violation guidelines to specifically address discharges into impaired waters. The goal of the referral guidelines is to reduce pollutant discharges into impaired waters in order to ultimately restore them to their full potential usage. To achieve this goal, enforcement actions are initiated earlier in an effort to improve the quality of waters which do not meet standards. If a stream is impaired by a pollutant and the permit limit for that pollutant is exceeded more than once in a running annual reporting period, formal enforcement action will be initiated against the discharger.